

WORKSHEET FOR HOT HALF ENQUIRY

◦ **PILLARS, SCREWS AND CENTERING RING:**

CENTERING PILLARS (C1): ϕ Q. ty (small diameter).

CENTERING PILLARS (C2): ϕ Q. ty (big diameter).

FIXING SCREWS (B): M = Q. ty

CENTERING RING (D): ϕ

◦ **ELECTRICAL SOCKETS AND LAYOUT:**

SOCKET TYPE:

PLEASE SUPPLY TEMPERATURE CONTROLLER ELECTRICAL LAYOUT

◦ **PLEASE STATE LOCATION OF:**

ELECTRICAL CONNECTIONS AND CONNECTORS

TOP OF MOULD

OPERATOR SIDE

(A) DIMENSION IN THE INJECTION POINT:

◦ **CLAMPING:** EMBEDDED PASSING THROUGH (G1)

EMBEDDED BLIND (G2)

OUT OF EDGE (G3)

IF CLAMPING IS OUT OF EDGE, PLEASE SPECIFY (F) DIMENSION

◦ **FOR COOLING FITTINGS, PLEASE SPECIFY:**

COOLING CONNECTIONS LOCATION SIDE

THREADS: not embedded (E2)

embedded (E1)

if embedded please specify ϕ Y:

THREADS TYPE: /..... GAS

thread M

◦ **PLEASE SPECIFY DIMENSION :**

hR =

hP =

(manifold thickness)

